

**OHAUS ELECTRONIC BALANCES**

The **OHAUS Adventurer Series** is an ideal balance for basic applications. Built for rugged use, these balances feature an easy to use three-button operation eliminating the need for any tedious personnel training. Features include push button calibration, large stainless steel weighing pan, ergonomic leveling system, RS232 bi-directional interface capabilities, weigh below capability and draft shield (on 150g and 310g models only). Functions include: parts counting. Weighing modes include: mg, g, Kg, lb, oz, ct, dwt and more. Analytical Balance: Ship wt 16 lbs. Ship Dims 21" L x 16" W x 22" H. Top Loading Balance: Ship wt. 14 lbs. Ship Dims 22" L x 16" W x 12" H. Specify 120V, 220V or 240V, 50/60Hz.

**TOP LOADING BALANCES**

Model No.	Capacity	Readability	Platform
AV510	510g	0.01g	7.1" Dia.
AV1500	1500g	0.01g	7.1" Dia.
AV3100	3100g	0.01g	7.1" Dia.
AV4100	4100g	0.1g	7.1" Dia.



**ANALYTICAL BALANCES - Includes Draft Shield**

Model No.	Capacity	Readability	Platform
AV150	150g	0.001g	3.9" Dia.
AV310	310g	0.001g	3.9" Dia.

The **OHAUS Navigator Series** offers the power of a laboratory balance in the style of a portable. Designed with contours for easy cleaning, Navigator has sealed front panels and spill rings to direct liquids off of the balance. The balance can be used with the supplied AC adapter (specify 120 or 220V, 50/60 Hz) or with 8-AA alkaline batteries (not included). Features of the Navigator include InCal™ (internal calibration), 4 cursor keys to "navigate" menus and functions, high contrast LCD display, large stainless steel weighing pans with windshields, auto shut-off, RS232 bi-directional interface capabilities, weigh below capabilities, menu & calibration lock out switches. Security device available. Functions include: parts counting, percent and animal weighing. Weighing modes include: mg, g, oz, lb, oz t, ct, dwt and more. Ship wt 6 lbs. Ship Dims 20" L x 11" W x 16" H.

Model No.	Capacity	Readability	Platform
NV32C	32g	0.002g	3" Dia.
NV210C	210g	0.01g	4.75" Dia.
NV410C	410g	0.01g	4.75" Dia.
NV610N*	610g	0.1g	4.75" Dia.
NV810C	810g	0.1g	4.75" Dia.
NV2100C	2100g	0.1g	5.5" x 6"
NV4100C	4100g	0.1g	5.5" x 6"
NV6100N*	6100g	1.0g	5.5" x 6"
NV8100C	8100g	0.5g	5.5" x 6"



Std. models shown have InCal™. \*Type Approved (NTEP) do not have InCal™. Also available without these features at reduced cost.

The **OHAUS Scout II Series** are portable, precision balances. Affordable with superior performance, these balances feature a large, high contrast LCD display, quick and easy two button operation, stainless steel weighing pan, ergonomic design, auto shut-off, low battery indicator and more. Security device available. Function for parts counting only. Weighing modes include: g, oz, ozt, dwt (lbs. for 1200 & 6000 models only). Ship wt 4 lbs. Ship Dims 11" L x 12" W x 6" H. Unit powered by supplied AC adapter (specify 120V or 220V, 50/60Hz) or one 9V battery (not included).

Model No.	Capacity	Readability	Platform
SC200	200g	0.01g	4.0" Dia.
SC400	400g	0.1g	5" x 5.75"
SC600	600g	0.1g	5" x 5.75"
SC1200	1200g	0.1g	5" x 5.75"
SC6000	6000g	0.1g	5" x 5.75"



Models with RS232 interfacing available - Call for quote.

**Accessories available for ALL Balances:**

Line Conditioner (for all balances) ..... No. LC1  
 Power Surge Protector (for all balances) ..... No. SP1