

SALA LADDER SAFETY SYSTEM

Our Ladder Safety System offers complete safety and security to workers who climb fixed ladders on grain bins, towers, etc. The popular LAD-SAF® flexible cable type system consists of a tensioned galvanized steel cable running the length of the climbing area, which is attached to the ladder structure by a top and bottom mounting brackets with cable guides. An easy to use detachable safety sleeve (3330) is connected to the workers body support (safety belt or full body harness) and attached to the cable, the worker then may ascend or descend without attending to the safety sleeve. Should the worker slip or fall, the safety sleeve locks onto the cable and prevents further movement until footing can be regained. The carabiner and body support must be ordered separately. For ladder lengths greater than 30 ft call for quote. Meets or exceeds industry standards: ANSI A14.3-1992, OSHA 1910.27, FAA RR-S-001301. CSA certified models available (Ref. Z259.2-M1979).



- Complete System for 30ft. Fixed Ladder with Mounting Brackets,
 Cable Guides, 3/8" Cable and 3330 Safety Sleeve. **No. LAD-SAF3**
- Single D-Ring Safety Belt with 3" Body Pad **No. 901**
 (Specify Size: S=32"-40", M=36"-44", L=40"-48", XL=44"-52")
- Same as above with Floating D-Ring **No. 9101FD**
- SAFLOK® Steel Carabiner, Self Closing & Self Locking - 2" Opening **No. SH108**
- Same with 1-3/16" Opening **No. SH106**
- Same with 3/4" Opening **No. SH523**
- Detachable Safety Sleeve (included in system) for use
 with 3/8" dia Cable **No. 3330**

FULL BODY HARNESES

Seedburo offers a complete range of Cross-Over Style and Vest Style Full Body Harnesses designed to retain the user in the event of a fall and distribute the impact forces throughout thighs, buttocks, chest and shoulders. These lightweight harnesses are available with many different optional features including: back D-ring (for fall arrest or restraint), front D-ring (for work positioning or ladder climbing), side D-rings (for restraint or work positioning), shoulder D-ring (for rescue and retrieval), non-sparking/nonconductive PVC coated hardware (for potentially explosive environments), Kevlar® webbing, stretch web, and more. Harnesses feature universal sizing. Full Body Harnesses meet or exceed industry standards: ANSI A10.14-1991, ANSI Z359.1-1992, OSHA 1910.66, OSHA 1926.502. CSA certified models are available (Ref. Z259.10-m90).

A. CROSS OVER STYLE

- Front/Back D-Rings, Pass Thru Buckle Leg Straps **No. 2010**
- Same as 2010 except with Non-Sparking/ Non-Conductive Hardware **No. 4351**
- Front/Back D-Rings, Tongue Buckle Leg Straps **No. 4382**
- Front/Back/Side D-Rings, Pass Thru Buckle Leg straps **No. 3270**
- Same as 3270 except with Tongue Buckle Leg Straps **No. 4082**
- Kevlar® 29 Webbing, Front/Back/Side D-Rings,
 Pass-Through Buckle Leg Straps **No. 3968**
- Stretch Web, Front/Back D-Rings, Pass Thru Buckle Leg Straps **No. 2700**

B. VEST STYLE

- Back D-Ring, Tongue Buckle Leg Straps **No. 2000**
- Back D-Ring, Pass Thru Buckle Leg Straps **No. 3321**
- Same as 3321 except with Belt Loops and
 Non-Sparking/Non-Conductive Hardware **No. 3805**
- Back D-Ring, Parachute Adjuster Leg Straps **No. 2001**
- Same as 2001 except with Shoulder D-Rings **No. 2001PS**
- Back/Side D-Rings, Pass Thru Buckle Leg Straps and Loops for Body Belt **No. 3512**
- Same as 3512 except with Tongue Buckle Leg Straps **No. 4232**
- Kevlar® 29 Webbing, Back D-Ring, Pass Thru Buckle
 Leg Straps, Non-Sparking / Non-Conductive Hardware **No. 3804**
- Stretch Web, Back D-Ring, Tongue Buckle Leg Straps **No. 2100**
- Stretch Web, Back/Side D-Rings, Pass Thru Buckle Leg Straps **No. 2208**

