

## FISHERBRAND™ TRACEABLE THERMOMETER

The Fisherbrand™ Flip-Stick™ Thermometer from Seedburo features an adjustable angle head of 45/90/135/180°, stainless steel sensor probe, memory recall, either F° or C° selectable readout, data hold/test function, low battery indicator and 16" lanyard.

The Flip-Stick™ has an easy-to-read ¾" digital display and a range of -58° to 572°F or -50° to 300°C. Resolution is 0.1° below 200°C and 1°C outside of this range. Accuracy is ±1° between -20° and +100°C. Unit operates on one (1) AAA battery (included) and is turned on or off by extending the probe.

The Flip-Stick™ is shipped with a Traceable™ Certificate of Calibration and the calibration complies with ISO 17025. The unit measures 11" with the probe fully extended and is 6"L x 1-7/8"W x 7/8"H when closed. Ship Dims 6.5" L x 2.5" W x 1" D, Ship Wt. 0.5 lbs.

Flip Stick™ Digital Traceable Thermometer ..... No. 06-664-26



## SEEDBURO SPECIAL DIAL THERMOMETER

2" Dial, 8" Stainless Steel Stem, Dual Temperature Range:

0 to 220°F / -10 to 100°C, Division: 2°F / 1°C ..... No. 2250R



## POCKET DIAL THERMOMETERS

Constructed of corrosion resistant stainless steel with 1" dial and 5" stem with recalibrator, plastic case and pocket clip. (Other ranges available, please call or write for prices).

0/ 220°F Range, 2° Divisions ..... No. 500R



## GLASS POCKET THERMOMETERS

Glass thermometer filled with non-toxic liquid spirit. Aluminum case with pocket clip. 6½" Long.

Range	Division	Model
0/120°F .....	1° .....	No. 212
0/220°F .....	2° .....	No. 212H
-5/45°C .....	0.5° .....	No. 212C
0/220°F and -20/110°C .....	2°/1° .....	No. 212D



## SEEDBURO SINGLE AND DUAL RANGE DIAL THERMOMETERS

Accurate readings are always obtained with these 3" and 5" bimetallic dial thermometers. Ruggedly built, these thermometers are constructed of stainless steel (type 304) casings and stems with heavy glass lenses and large black figures. All thermometers have ¼" dia. stems with ½" NPT connections, nut-type recalibrator and accuracy to 1% of span. (Other dial sizes and stem lengths are available. Please call or write for prices.)

Single and Dual Temperature Ranges Available:

-40/160°F	0/220°F	25/125°F	50/300°F	50/500°F
-40/70°C	-10/100°C	0/50°C	10/150°C	10/250°C

3" Dial, 2½" Stem .....	No. 3000R2
3" Dial, 4" Stem .....	No. 3000R4
3" Dial, 6" Stem .....	No. 3000R6
3" Dial, 9" Stem .....	No. 3000R9

(Specify temperature range: dual or single, °F or °C when ordering)



## SEEDBURO GLASS GRAIN, NIST TRACEABLE AND REFILL THERMOMETERS

Part No.	Description	Length	Temp. Range	Divisions	Immersion	Traceable to NIST
No. 208	Seedburo Easy-Read	12"	0 to 120°F	1°		
No. 30591	Enviro-Safe®	200mm	-10 to 110°C	1°	50mm	YES
No. 30597	Enviro-Safe®	200mm	0 to 230°F	2°	50mm	YES
No. 212R	Glass Refill	5-3/8"	0 to 120°F	1°		
No. 212HR	Glass Refill	5-3/8"	0 to 220°F	2°		
No. 212CR	Glass Refill	5-3/8"	-5 to 45°C	.5°		
No. 212DR	Glass Refill	5-3/8"	0 to 220°F / -20 to 110°C	2°/1°		

U.S. / Canada

Toll Free: 1-800-284-5779

Fax: 312-738-5329

International: 312-738-3700