



Size to Order	HP	Weight (Lbs.)	Model Number
10'	0.5	175	No. HR10
11.5'	0.5	190	No. HR11
13'	0.5	205	No. HR13
15'	0.5	225	No. HR15
17'	0.5	245	No. HR17
19'	0.5	270	No. HR19
21'	0.5	285	No. HR21

OPTIONAL EQUIPMENT FOR MODEL R

Two Rubber Wheels	No.	HRW
Stand with Rubber Wheel & Locks	No.	HRWL
Undercarriage	No.	HRUC
Roller Carriage		



The Model "R", besides being extremely convenient (it can be folded in half), is also extremely versatile. Conveying uses include: truck, loft or freight car, floor-tofloor, stairway, or as a portable booster with a wheel or roller conveyor. Suitable for bag handling, bag and carton stacking, and moving cartons, cases, and boxes.

CONVEYORS INCLUDES:

- Black Trackmate 447 Roughtop w/PVC Cover - 12" Wide
- 18" Wide Aluminum Bed
- 115/230V, 60 Hz, 1PH Enclosed Motor (specify requirements)
- 65 FPM Constant Belt Speed
- Reversing Drum Switch
- 20' Power Cord with Plug.



CONVEYOR INCLUDES

- Black Trackmate 447 Roughtop w/PVC Cover-14" Wide with Two 1- 1/2" Dia. x 1" Hardwood Cleats Spaced every 60"
- 4" Deep x 20" Wide x 12 Ga. Slider Red
- Welded Steel Base
- 4" Dia. Steel Swivel Casters (10' to 16' Lengths)
- 6" Dia. Steel Swivel Casters (20' and 22' Lengths)
- Powered Screw Raising Device
- 115/230V, 60 Hz, 1PH Totally Enclosed Motor (specify requirements)
- 65FPM Constant Belt Speed
- Reversing Drum Switch
- 20' Power Cord With Plug.

HYTROL MODEL B/BL PORTABLE FOLDING "CLEATED" CONVEYOR

Ideal for stacking, loading, and unloading. Cleats permit use at inclines up to 45°. Complete with portable base. "BL" conveys material from one floor to another or to a balcony area. Long bed extends into a truck, reducing distance for loading the conveyor. Lever control easily adjusts angle. Angle automatically locked by powered screw.

Size to	H.P.	Weight	Model
Order		Lbs	No.
10'	3/4	545	HB10
12'	3/4	590	HB12
14'	3/4	650	HB14
16'	3/4	695	HB16
20'	1	930	HBL20
22'	1	990	HBL22

HYTROL MODEL BA PORTABLE FOLDING "BOOSTER" BELT CONVEYOR



- **CONVEYOR INCLUDES:** Black Trackmate 447 Roughtop w/PVC Cover-14" Wide
- 4" Deep x 20" Wide x 12 Ga. Slider Bed
- Welded Steel Base
- 4" Dia. Steel Swivel Casters (10' to 16' Lengths)
- 6" Dia. Steel Swivel Casters (20' and 22'
- Powered Screw Raising Device
- 115/230V, 60Hz, 1PH Enclosed Motor (specify requirements).

Size to	H.P.	Weight	Model
Order		Lbs	No.
10'	3/4	560	HBA10
12'	3/4	600	HBA12
14'	3/4	650	HBA14
16'	1	700	HBA16
20'	1	940	HBA20
22'	1	990	HBA22

OPTIONAL EQUIPMENT FOR MODEL B, BL & BAL

4-6" Dia. Rubber Swivel Casters	. No. HBRSC
2 - Floor Locks	. No. HBFL
Guard Rails Both sides per foot	. No. HBGR

U.S. / Canada Toll Free:

1-800-284-5779 **Fax:** 312-738-5329 **International**: 312-738-3700