

SEEDBURO GIANT WHIRLWIND MIXERS

Mixes whole grains, seeds, mineral and feed concentrates quickly and easily. Ideal for custom mixing. Dependable, fast and thorough. Just ten minutes produces an even blend of all ingredients after the last batch is dumped into the hopper. Handles large capacity or small batch mixing. Constructed of heavy gauge steel. Seams are electrically welded and dust proof. Legs are 2" x 2" x 1/8" angles rigidly braced. Mixers are equipped with shaft, motor pulleys and V-belts. Bearings have zerk fittings for easy greasing. Mixers do not include motor.

Exclusive "whirlwind" mixing paddle at top of conveyor shaft increases mixing speed and insures perfect blending. Ingredients are loaded into hopper at bottom. Vertical crew conveyor revolves rapidly, lifting ingredients to top where mixing paddle whirls particles to wall of mixing chamber. After falling to the bottom, they are elevated and whirled again and again. Once mixing is complete loading hopper swings to one side, where it is out of the way while sacking. Attach sack over lower flanges of sacker spout and pull out slide. When sack is full, push slide back in place.



Cu. Ft. Capacity	Capacity Pounds*	Overall Height	Drum Ht.	Drum Dia.	Auger Dia.	Floor Space Required	Motor** Required	Ship Wt	Model
30.2	1057	96½"	91"	40"	7"	36" Tri.	3 HP	482 lbs	1700V
51.6	1806	95"	87"	53"	10"	46¼" Tri.	3 HP	658 lbs	1234V
70.8	2478	108¾"	101"	61"	12"	44¾" Sq.	5 HP	1017 lbs	2934V
108.0	3780	131¾"	124"	61"	12"	45¾" Sq.	7½" HP	1294 lbs	3834V
132.0	4620	131¾"	124"	72"	12"	55¾" Sq.	7½" HP	1549 lbs	4934V

*Based on 35 lbs per cubic foot of material

**Motors not included.

SEEDBURO QUIK-MIX

The Quik-Mix is a proven performer for dry material mixing and color blending. The direct drive vertical auger creates a unique blending action to ensure a complete, uniform mix every time. In most cases, pelletized and granular material batches can be mixed in five minutes or less.

The materials to be mixed are loaded from either side of the Quik-Mix. Special scoop blade at bottom of auger shaft draws material into bottom of auger tube. Disperser blade at top of auger shaft spreads materials across top of hopper to help create an even blend of ingredients. The slide gate at the bottom of the hopper discharge the materials. Sloped sides of mixer help to ensure complete clean out.



Constructed of 14-gauge steel with built-in 2-way entry pocket for fork lift. Piano-hinged, center-mounted covers allow loading from either side. Large, positive seal 8" diameter slide gate allows quick and complete emptying of the mixer. Lock gate prevents spillage while hopper is in transit. The Quik-Mix comes equipped with a large on/off switch located conveniently at the top beam of the Mixer. The Mixer is also equipped with a digital readout timer that allows the operator to perform other tasks without the risk of over mixing the batch. 350 lbs. capacity. Drum Dims. 48" W x 38" H. Ship wt. 420 lbs. Dims. 60" L x 60" W x 60" H.

Quik Mix, 115V, 60Hz, 1PH	No. QM26
Quik Mix, 220V, 50Hz, 1PH	No. QM26/C
Export Crating, Wooden Box	No. QM/EX

Optional Equipment:

Bag Break for 48" dia. Quik Mix	No. QM-BB
Quik Mix Stand, 44" x 44" x 52"	No. QM-STAND
Personnel Platform: Platform, Ladder & Railing	No. QM-PP
Export Crating for Stand	No. QM-STAND/EX

U.S. / Canada

Toll Free: 1-800-284-5779

Fax: 312-738-5329

International: 312-738-3700