

**Standard Equipped Model:**

- Overshot style spiked-tooth cylinder, 12" dia. x 20" wide
- Winnowing blower
- Shaker assembly pan & tail rake
- Spiked-tooth concave w/adjustable clearance
- 9HP gas engine with rewind starter
- Mounted on trailer assembly w/running lights
- Variable speed threshing cylinder
- 24" x 14" feeding hopper (accessible from operator's platform)
- Operators platform with ladder

**LARGE VOGEL STATIONARY PLOT THRESHER**

The Seedburo Large Vogel Plot Thresher is a large volume, multi-crop machine for threshing small grains, cereals, forages and legumes. Used by researchers all over the world, the design of the SLVPT has been proven for over 30 years. Benefits include simple operation, low maintenance and easy interior inspection. Dims, standard equipped: 99" L x 50" W x 85" H w/axle. Net wt. 1350 lbs. Ship wt. Domestic 1700 lbs. Export 1800 lbs.

Large Vogel thresher with overshot spiked tooth cylinder & concave .....	<b>No. SLVPT-OS/G</b>
Large Vogel thresher with metal raspbar cylinder & concave .....	<b>No. SLVPT-MR/G</b>
Large Vogel thresher with rubber faced raspbar cylinder & concave .....	<b>No. SLVPT-RR/G</b>
Rubber cushion axle .....	<b>No. SLVPT-RC</b>
Electric start for gas engine .....	<b>No. SLVPT-ES</b>
Domestic Crating .....	<b>No. SLVPT/DOM</b>
Export Crating .....	<b>No. SLVPT/EX</b>
<b>(Electric motor or diesel engines available upon request)</b>	

**Standard Equipped Model:**

- Overshot square spiked cylinder
- Feeding hopper
- Variable speed threshing cylinder
- Turn signals and reflectors
- Tail light assembly with stop light
- Shaker pan and tail rake
- Solid straight axle
- 8HP Briggs and Stratton gas engine.

**MEDIUM VOGEL PLOT THRESHER**

A medium capacity thresher, similar in design and operation to the Large Vogel Plot Thresher. Feeding tray is easily accessible from ground level. Available with choice of shaker/tail rake, or shaker/sieve assembly for threshing multiple crops. Thresher is mounted on a trailer assembly with running lights. Dims, standard equipped: 103" L x 50" W x 60" H w/axle. Net wt. 1000 lbs. Ship wt. Domestic 1100 lbs. Export 1200 lbs.

Medium Vogel thresher with overshot spiked-tooth cylinder & concave .....	<b>No. SMVPT-SS/G</b>
Medium Vogel thresher with round spiked cylinder & concave .....	<b>No. SMVPT-RS/G</b>
Medium Vogel thresher with rubber faced raspbar cylinder & concave .....	<b>No. SMVPT-RR/G</b>
Medium Vogel thresher with metal raspbar cylinder & concave .....	<b>No. SMVPT-MR/G</b>
No. 10MM Graepel sieve for cereals in lieu of tail rake .....	<b>No. SMVPT-10</b>
No. 18MM Graepel sieve for beans, sunflower, peas in lieu of tail rake .....	<b>No. SMVPT-18</b>
Rubber cushion axle in lieu of straight axle .....	<b>No. SMVPT-RC</b>
Electric start for gas engine .....	<b>No. SMVPT-ES</b>
Optional air compressor .....	<b>No. SMVPT-AC</b>
Domestic Crating .....	<b>No. SMVPT/DOM</b>
Export Crating .....	<b>No. SMVPT/EX</b>
<b>(Electric motor or diesel engines available upon request)</b>	

**When specifying options for Seedburo threshers, please consider the following guidelines:**

- Threshers with overshot-style cylinders and concaves require the use of interchangeable configurations to provide the correct threshing action for different crops.
- Often, more than one cylinder and concave style can be used for a single crop.
- A more aggressive configuration provides efficient, fast threshing.
- A less aggressive configuration will provide gentle seed handling.
- With any configuration, the aggressiveness of the cylinder can be controlled to some extent by varying the cylinder speed.