

SMALL BUNDLE THRESHER

The Small Bundle Thresher will thresh small sheaves of grains and single plants. The 11" wide intake housing permits greater threshing efficiency without sacrificing sample purity. A removable recleaning pan with four interchangeable screens is provided. Screen sizes are 1/8", 1/4", 3/8" and 1/2" mesh. Cylinder and blower speeds are adjustable via interchangeable pulleys. Dims, standard equipped: 31" L x 31" W x 49" H. Net wt. 250 lbs., Ship wt. 320 lbs.

Standard Equipped Model:

- · Square spiked cylinder-overshot style
- Square spiked concave
- 6" diameter x 14" wide cylinder
- Feeding hopper



- · Auxiliary beater and strawpuller
- · Hand truck-type handles
- · Safety cover guard screens
- 3HP air-cooled gas engine
- Bladed type winnowing blower with adjustable air intake

Thresher with square spiked cylinder & concave	No. SSBT-RS/G No. SSBT-RR/G No. SSBT-RC/G
Thresher with square spiked cylinder & concave	. No. SSBT-SS/B
Thresher with round spiked cylinder & concave	
Thresher with rubber raspbar & rubber coated steel raspbar concave	
Thresher with rubber coated raspbars	
Thresher with metal raspbars	
Electric motor, 1 HP 220V, 50Hz in lieu of gas engine.	
Thresher with square spiked cylinder & concave	No. SSBT-SS/C
Thresher with round spiked cylinder & concave	No. SSBT-RS/C
Thresher with rubber raspbar & rubber coated steel raspbar concave	
Thresher with rubber coated raspbars	No. SSBT-RC/C
Thresher with metal raspbars	
Domestic crating	No. SSBT/ DOM
Exporting crating	

SINGLE PLANT AND HEAD THRESHER

This unit is suitable for threshing single plants and heads of small cereal grains. The Seedburo SSVPT is easily inspected and self-cleaning between plots; cylinder speed is via step pulleys. The wagon assembly provides easy mobility. Dims, standard gas equipped: 44" L x 20" W x 44" H. Electric model: 42" L x 20" W x 44" H. Net wt. 185 lbs., Ship wt. 260 lbs.

Standard Equipped Model:

- · Square spiked overshot style, cylinder and concave
- Safety cover guard screens
- Auxiliary beater and strawpuller
- · V pulleys and belts
- 4.5" dia. x 6" wide cylinder
- · Side sacking chute & grain catch pan

- · Feeding hopper
- Wooden base with coaster wagon
- 3HP air cooled gas engine truck assembly
- Grain rebounding baffle
- 4 10" rubber tired wheels (14.5" wheel track)
- 360 C.F.M. winnowing blower with adjustable baffle



Thresher with square spiked cylinder & concave	No.	SSVPT-SS/G
Thresher with round spiked cylinder & concave	No.	SSVPT-RS/G
Thresher with rubber raspbar & rubber coated steel raspbar concave		
Thresher with rubber coated steel raspbars		
Thresher with metal raspbars		
Electric motor, ¾ Hp 110V, 60Hz in lieu of gas engine.		0011 1 11111/0
Thresher with square spiked cylinder & concave	No	CCVDT CC/D
Thresher with round spiked cylinder & concave		
Thresher with rubber raspbar & rubber coated steel raspbar concave		
Thresher with rubber coated steel raspbars	No.	SSVPT-RC/B
Thresher with metal raspbars	No.	SSVPT-MR/B
Electric motor, ¾ Hp 220V, 50Hz in lieu of gas engine.		
Thresher with square spiked cylinder & concave	No.	SSVPT-SS/C
Thresher with round spiked cylinder & concave	No.	SSVPT-RS/C
Thresher with rubber raspbar & rubber coated steel raspbar concave	No.	SSVPT-RR/C
Thresher with rubber coated steel raspbars		
Thresher with metal raspbars		
Domestic crating (plywood box)		
, , , , , , , , , , , , , , , , , , ,		
Export crating (plywood box)	No.	SSVP1/EX