

## “ACHIEVA” PRECISION TABLE TOP GERMINATOR

Seedburo’s Achieva tabletop germinator offers features similar to our larger units, but these will save you both space and money! The ATTGPT is ideal for small volume seed labs that require precision, but do not require a full size germinator.

Features include separate set-point digital controllers for hot and cold cycles. A single dual stage, digital timer controls both the selection for single mode operation or dual mode operation. The controller allows for automatic mode switching. Temperature range is between 30F° and 120F°/1°C and 49°C. Digital display temperature showing both set-point and actual cabinet temperature. Lighted cycles help to perform photo tests with excellent refraction from white interior and stainless steel door liner. An internal fan distributes air evenly and gently with minimal temperature stratification. Heat is maintained by a long-life, stainless steel, low watt density heating element. Uniform cooling is maintained through the use of an air cooled hermetically sealed condenser compressor unit. The ATTGPT is a dry style germinator designed for containerized germination testing.

Two open wire shelves, 20” x 14” at 2-1/2” spacing, are included. Interior dims are 19” D x 20.75” W x 24.5” H. Exterior dims are 24” L x 24” W x 37” H. Ship Wt. 84 lbs. Ship Dims. 24” L x 24” W x 39” H. Export boxed wt. 244 lbs. Ship Dims. 31” L x 28” W x 45” H.



Achieva Table Top Germinator, 115V, 60Hz .....	No. ATTGPT/B
Achieva Table Top Germinator, 220V, 50Hz .....	No. ATTGPT/C
Required Domestic Boxing .....	No. ATTGPT/DOM
Required Export Boxing .....	No. ATTGPT/EX

## SEEDBURO LIGHT-DARK GERMINATOR

A clear, angled plexiglass top allows light in and any condensation formed drains off without dripping on the samples. Stainless steel inside and out. High-density foam provides a non-absorbent, insect free thermal barrier to provide an even temperature within the chamber. Eight aluminum 15” x 21” trays are included, providing a total of 2520 square inches of testing area. A water/ice pan is included. Fill with water or ice when additional humidity or below ambient temperatures are required. A thermostatically controlled heat element maintains even temperatures up to 104° F (40° C) ± 1° C. Thermometer, lighted on-off switch and rubber feet are standard. Net wt. 82 lbs. Ship wt. 88 lbs. Dims. 24” L x 18” W x 26-1/2” H. Ship Dims. 28” L x 22” W x 28” H. **MADE IN USA**



L-D Germinator, 110V, 50/60Hz, 1PH .....	No. 548
L-D Germinator, 220V, 50/60Hz, 1PH .....	No. 548/A
Replacement Thermometer .....	No. 548T
Replacement Heating Element, 110V .....	No. 54H
Replacement Heating Element, 220V .....	No. 54H/A
Replacement Thermostat .....	No. 54TR
Replacement Tray .....	No. 548-TRAY